L3 Ceiling Style

LP-L3-60X60 OM DALI 840

Art. No 542431138





1	40 40 40 40
100	
1	
	45 45 45 4
1/6	THE REPORT OF


Luminous flux	4100 lm
Luminaire efficiency	114 lm/W
CRI	> 80
Correlated colour temperature	4000 K
Rated power	36 W
LED	Samsung LM561B
Dimmable	YES - to 1%
Input current	0.157 A
Working voltage	AC 220-240 V
Ingress protection code	IP20
Mech. impact protection code	-
Working temperature	-20 to +40°C

cd/klm C0 - C1	80 —— C90 - C270		η = 1009
30°	15°)° 15°	30
/	61	00	
\ /			
×	5	00	
45°	4	00	45
	3	00	
600			60
	20	00	X
-75°	$\times \times / \setminus$		75
			+1
90°			90
105°	X	1/ /	105

Service life	80 000 hours at 80% luminous flux
Housing	Steel Sheet
Diffuser	Polystyrol
Installation	Surface mounting
Dimensions – LxWxH	622x622x85 mm
Weight	-
Mark	CE, RoHS
Origin	EU



Dimensional drawing:



Solar LED Power Ltd. is constantly developing and improving its products. The right is reserved to change specifications without prior notification.