
## L5 Linear Style

## LP-L5-P120-192 PWM 830

Art. No 552341200








| Luminous flux                 | 6720 lm        |
|-------------------------------|----------------|
| Luminaire efficiency          | 112 lm/W       |
| CRI                           | > 80           |
| Correlated colour temperature | 3000 K         |
| Rated power                   | 60 W           |
| LED                           | Samsung LM561B |
| Dimmable                      | YES - to 10%   |
| Input current                 | 0.26 A         |
| Working voltage               | AC 220-240 V   |
| Ingress protection code       | IP20           |
| Mech. impact protection code  | -              |
| Working temperature           | -30 to +40°C   |

| Service life       | 100 000 hours at 80% luminous flux          |
|--------------------|---|
| Housing            | Aluminium                                   |
| Diffuser           | PMMA  |
| Installation       | Surface mounting or suspended on wire/chain |
| Dimensions – LxWxH | 1235x124x93 mm                              |
| Weight             | 2.3 kg                                      |
| Mark               | CE, RoHS                                    |
| Origin             | EU  |
| Manufacturer       | Solar LED Power Ltd.                        |



## Dimensional drawing:



Solar LED Power Ltd. is constantly developing and improving its products. The right is reserved to change specifications without prior notification.