## L5 Linear Style

## LP-L5-P60-144 DALI 830

Art. No 552331242





| 105°               | 47 4            | 105            |
|--------------------|-----------------|----------------|
| 90°                |                 | 90             |
| 75°                |                 | 75             |
| 60°                | 200             | 60             |
| 45°                | 300             | 45             |
| 7                  | 400             |                |
| 30°                | 15° 0°          | 15° 30°        |
| cd/klm<br>C0 - C18 | 0 —— C90 - C270 | $\eta = 100\%$ |

| Luminous flux                 | 4480 lm        |
|-------------------------------|----------------|
| Luminaire efficiency          | 112 lm/W       |
| CRI                           | > 80           |
| Correlated colour temperature | 3000 K         |
| Rated power                   | 40 W           |
| LED                           | Samsung LM561B |
| Dimmable                      | YES - to 1%    |
| Input current                 | 0.173 A        |
| Working voltage               | AC 220-240 V   |
| Ingress protection code       | IP20           |
| Mech. impact protection code  | -              |
| Working temperature           | -30 to +40°C   |

| Service life       | 100 000 hours at 80%<br>luminous flux       |
|--------------------|---|
| Housing            | Aluminium                                   |
| Diffuser           | PMMA  |
| Installation       | Surface mounting or suspended on wire/chain |
| Dimensions – LxWxH | 633x124x93 mm                               |
| Weight             | -   |
| Mark               | CE, RoHS                                    |
| Origin             | EU  |
| Manufacturer       | Solar LED Power Ltd.                        |



## Dimensional drawing:



